



## BFCL450

### TECHNICAL SHEET

#### GENERAL

Weight of basic machine (approx.) [Kg]  
Feeding speed (max) [m/min]  
Feeding accuracy [mm]

#### BFCL450

6500  
270  
0,01

#### DEREELER

Number devices [Q.ty]  
Clamping range (min/max) [mm]  
Outer coil diameter (max) [mm]

2  
470/520  
1000

#### STRIP OF ELECTRICAL STEEL

Thickness (min/max) [mm]  
Width (min/max) [mm]  
Length (min/max) [mm]

0,18/0,35  
40/450  
350/2000

#### CUTTING DEVICES

Puching group  
V-notching group [Q.ty]  
Swivelling shearing group [Q.ty]  
(Three working position 45° 90° 135°)  
Fixed shearing group  
(Three working position 45° 90° 135°)

1  
1  
1  
1  
Not available

#### STACKING GROUP (OPTIONAL)

Roof stacker [Q.ty]  
Number of stacking positions [Q.ty]

1  
2

#### AUTOMATIC STACKING GROUP (OPTIONAL)

Number of stacking levels  
Number of stacking carriages for each level

2  
2

#### OFF-LINE STACKING ROBOTS AND TILTING TROLLEYS (OPTIONAL)

Number of tilting stacking trolley  
Number of stacking robots

2  
2

BF S.r.l.

Via della Scienza ,21 - 36070 Castelgomberto (VI) - Italy  
Tel: +39 04 45 44 09 61 - Fax: +39 04 45 44 51 28  
www.bf-e.eu - info@bf-e.eu